

30" *precision series*[™]

Manual Clean



GCR305

30" RANGE-TOP FEATURES

- 140 Deg. Simmer – 19,000 BTU Power-Flo[™] burners (sealed)*
- 800 – 25,000 BTU Power-Wok[™] burner*
- Integrated reversible wok grate*
- Full extension Drip Trays on EZ-Glides*
- Stay-Cool[™] die cast, chrome plated metal knobs*
- Auto-ignition/re-ignition on all burners
- Stainless steel BBQ grill and griddle covers come standard
- Smooth-top continuous cast iron grates with easy to clean matte porcelain finish
- Island trim included

30" OVEN FEATURES

- Convection oven
- Large 4.1 cu. ft. oven cavity – 24" W X 14" H X 21" D
- 18,000 BTU infrared broiler behind glass
- 30,000 BTU oven for uniform baking
- Adjustable rear casters for easy installation

30" OVEN FEATURES (continued)

- Adjustable front legs for easy leveling
- Titanium speck porcelain oven interior*
- 25-Watt bright oven lights
- 3 rack positions w/ 3 racks provided
- Broil pan provided
- 1-1/4" thick professional-style handle
- Heavy-duty oven door hinges
- Extra large viewing window w/ embossed design

OVEN MODES

Bake, broil, convection bake, convection broil, open-door broil

OTHER OVEN USES

Defrost, preheat, warm, slow cooking, normal thawing, advanced thawing

* Capital Exclusive Feature



Capital exclusive feature:
Power-Flo™ burners.
19,000 BTU - 140 deg. simmer



Infrared glass broiler




25,000 BTU Power-Wok™




Optional cabinet red knobs

GAS CONVECTION MODELS AVAILABLE (NON-SELF-CLEAN)*



GCR304 – 30" four burner
gas convection range



GCR305 – 30" five
burner gas convection
range w/ wok burner

* Available in Natural Gas and Liquid Propane

AVAILABLE ACCESSORIES

- Conversion kits
- CRK30 – cabinet red knobs for 30" range
- P30SLB – 9" stainless steel wall mount low back
- Wok ring

COMPLIMENTARY PRODUCTS

- PSVH30L – 30" Performance Series vent hood w/ 600 CFM blower + lights
- Duct covers
- GRT24WK – 24" 30,000 BTU built in Power-Wok™ range-top
- GRT30Q – 30" 40,000 BTU built in Infra-Q™ infrared BBQ-grill

SHIPPING WEIGHT

250-275 LBS

ELECTRICAL RATINGS

VOLTAGE	CURRENT/POWER	FREQUENCY
120 VAC	20 AMP	60 HZ

GAS RATINGS

	NATURAL GAS	PROPANE
Manifold pressure:	5.0" W.C.	10" W.C.

OTHER

- "0" clearance base cabinet installation
- Field convertible to LP or NG depending on gas type
- ETL certified for USA and Canada
- 2 years full parts and labor covers entire product (conditions apply)

CABINET PREPARATION

